## **BUILDING SIZE**

172,685 RSF Amenity floor: 7,150 SF interior, 4,300 SF amenity terrace

#### OUTDOOR SPACE

4,300 SF amenity terrace 250 SF private terrace on floors 15, 17, 19, 21, 23, 25, 27, 29

# **CEILING HEIGHT**

Typical floor: 14'-3"-14'-6" slab to slab, 13'-5"-13'-8" floor to underside of slab Finish ceiling: 11'-0" - 11'-3" Double height area: 27'-8" floor to underside of slab (floor 15-16)

## HVAC

Cooling is provided through cooling towers and water cooled DX Cooling units per floor for tenant connection with MERV 14 filters; Outside Air incoming stream with both MERV 8 and MERV 14 filters; Heat is provided by gas fired hot water condensing boilers with hot water pumps and plate and frame heat exchangers. Capped hot water piping for tenant connection.

## LIFE SAFETY

The building is fully sprinklered with full fire alarm coverage.

### **SUPPLEMENTAL** COOLING

Secondary Condenser Water Supply and Return capped outlets for tenant use.

# CONSTRUCTION

The building is a reinforced concrete structure that has a side core. The building envelope is a curtain wall system with full-height triple-glazed vision glass on all office floors.

# ELECTRIC

Step-up transformers are provided for elevators and mechanical loads. The office levels are provided with electrical power density of 6 W/USF.

## **SECURITY**

24/7 Security Guards with visitor management and camera security coverage.

### EMERGENCY GENERATOR

All life safety systems are on a 1000 KW diesel generator.

# TELECOM

There is an IDF (Intermediate Distribution Frame) room on each floor for tenant connection.

#### AMENITIES

7,150 SF amenity floor including a lounge, private meeting rooms, state-of-the-art conference center, event space with catering kitchen, and a 4,300 SF amenity terrace.

Bicycle storage on ground floor.

# **FLOOR LOADS**

50 LBS/RSF live load

## DOMESTIC WATER FILTRATION

Domestic Water is filtered at building point of entry.

## **ELEVATORS**

4 Passenger Elevators with destination dispatch technology. Three elevators with 3,500 lbs capacity and one with 4,500 lbs capacity.

## ACCESSIBILITY

Fully ADA compliant

LEED Targeting LEED Gold